

Printing date 16.12.2013 Version number 3 Revision: 16.12.2013

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Osmo Maintenance Oil

Article number: 3079, 3081, 3098

1.2 Relevant identified uses of the substance or mixture and uses

advised against No further relevant information available.

Application of the substance / the

preparation Maintenance product

Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG

Affhüppen Esch 12 D-48231 Warendorf

Further information obtainable

from: Product safety department

Phone: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone

number: emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German

and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to

Regulation (EC) No 1272/2008 The product is not classified according to the CLP regulation.

Classification according to

Directive 67/548/EEC or Directive

1999/45/EC Not applicable.

Information concerning

particular hazards for human and

environment: The product has to be labelled due to the calculation procedure of the "General

Classification guideline for preparations of the EU" in the latest valid version.

Classification system: The classification is according to the latest editions of the EU-lists and extended by

company and literature data.

2.2 Label elements

Labelling according to Regulation

(EC) No 1272/2008VoidHazard pictogramsVoidSignal wordVoidHazard statementsVoid

(Contd. on page 2)



Printing date 16.12.2013 Version number 3 Revision: 16.12.2013

Trade name: Osmo Maintenance Oil

(Contd. of page 1)

Precautionary statements P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P262 Do not get in eyes, on skin, or on clothing. P271 Use only outdoors or in a well-ventilated area.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

Additional information: Observe the general safety regulations when handling chemicals.

Contains 2-butanonoxime. May produce an allergic reaction.

Safety data sheet available on request.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.*vPvB*: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 64742-47-8	aliphatic hydrocarbons, C13-C18	25-50%
EC number: 921-050-8	X n R65	
Index number: 649-422-00-2		
Reg.nr.: 01-2119485032-45	♦ Asp. Tox. 1, H304	
CAS: 64742-48-9	aliphatic hydrocarbons, C10-C13	25-50%
Index number: 649-327-00-6	▼ Xn R65	
Reg.nr.: 01-2119457273-39	R66	
	♦ Asp. Tox. 1, H304	
CAS: 34590-94-8	(2-methoxymethylethoxy)propanol	≤ 2.5%
EINECS: 252-104-2	substance with a Community workplace exposure limit	
Reg.nr.: 01-2119450011-60		
Additional information:	For the wording of the listed risk phrases refer to section 16.	•

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

After inhalation: Supply fresh air; consult doctor in case of complaints.

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult

doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)



Printing date 16.12.2013 Version number 3 Revision: 16.12.2013

Trade name: Osmo Maintenance Oil

(Contd. of page 2)

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: If swallowed, seek medical advice immediately and show this container or label.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and

effects, both acute and delayed 4.3 Indication of any immediate

medical attention and special

No further relevant information available.

treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant

foam.

5.2 Special hazards arising from

the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures Keep away from ignition sources.

Ensure adequate ventilation

6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for

containment and cleaning up: Warm water and cleansing agent

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Prevent formation of aerosols.

Keep away from heat and direct sunlight.

Keep receptacles tightly sealed. Use only in well ventilated areas.

Information about fire - and

explosion protection: Keep ignition sources away - Do not smoke.

(Contd. on page 4)



Printing date 16.12.2013 Version number 3 Revision: 16.12.2013

Trade name: Osmo Maintenance Oil

(Contd. of page 3)

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

storerooms and receptacles: Store in a cool location.

Store only in the original receptacle.

Information about storage in one

common storage facility: Do not store together with alkalis (caustic solutions).

Do not store together with oxidizing and acidic materials.

Further information about

storage conditions: Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about

design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

64742-48-9 aliphatic hydrocarbons, C10-C13

TWA (8 H) Long-term value: 1.000 mg/m³, 150 ppm ppm

Source: UK SIA

34590-94-8 (2-methoxymethylethoxy)propanol

WEL Long-term value: 308 mg/m³, 50 ppm

Sk

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment: General protective and hygienic

measures: Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Do not eat, drink, smoke or sniff while working.

Avoid contact with the eyes and skin.

Do not carry product impregnated cleaning cloths in trouser pockets.

Respiratory protection: Use suitable respiratory protective device only when aerosol or mist is formed.

Not necessary if room is well-ventilated.

Protection of hands: Protective gloves and protective skin cream

The glove material has to be impermeable and resistant to the product/ the substance/

the preparation.

Selection of the glove material on consideration of the penetration times, rates of

diffusion and the degradation

To avoid skin problems reduce the wearing of gloves to the required minimum.

(Contd. on page 5)

GB



Printing date 16.12.2013 Version number 3 Revision: 16.12.2013

Trade name: Osmo Maintenance Oil

(Contd. of page 4)

Material of gloves The selection of the suitable gloves does not only depend on the material, but also on

further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be

calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective

gloves and has to be observed.

For the permanent contact gloves made of the following materials

are suitable: Nitrile rubber, NBR

Eye protection: Goggles recommended during refilling

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Fluid

Colour: According to product specification

Odour: Characteristic

Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: Undetermined.

Flash point: >60 °C °C (DIN 53213)

Ignition temperature: 210 °C

Self-igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Density at 20 °C: 0.85-0.95 g/cm³ (DIN 51757)

Solubility in / Miscibility with

water: Not miscible or difficult to mix.

Viscosity:

Kinematic at 20 °C: 40-60 s (DIN 53211/4)

9.2 *Other information* No further relevant information available.

(Contd. on page 6)

GB



Printing date 16.12.2013 Version number 3 Revision: 16.12.2013

Trade name: Osmo Maintenance Oil

(Contd. of page 5)

SECTION 10: Stability and reactivity

10.1 Reactivity

10.2 Chemical stability
Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous

reactions Reacts with fabric soaked in the product (e.g. cleaning wool).

10.4 Conditions to avoid No further relevant information available.10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition

products: Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Additional information: Warning:

Wash out any used cloth impregnated with this product immediately after use or store

in an airtight container (danger of self-ignition)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

LD/LC50 values relevant for classification:				
64742-47-	8 aliphatic	hydrocarbons, C13-C18		
Oral	LD50	> 10000 mg/kg (rat)		
Dermal	LD50	> 3000 mg/kg (rabbit)		
Inhalative	LC50 / 4h	> 6200 mg/l (rat)		
64742-48-9 aliphatic hydrocarbons, C10-C13				
Oral	LD50	> 5000 mg/kg (rat) (OECD 401)		
Dermal	LD50	> 5000 mg/kg (rat) (OECD 402)		
	LC50 / 4h	> 5 mg/l (rat) (OECD 403)		

Primary irritant effect:

on the skin: No irritant effect.on the eye: No irritating effect.

Sensitization: Sensitizing effect by skin contact is possible by prolonged exposure.

Additional toxicological

information: The product is not subject to classification according to the calculation method of the

General EU Classification Guidelines for Preparations as issued in the latest version.

Sensitisation Contains 2-butanonoxime. May produce an allergic reaction.

(Contd. on page 7)

GE



Printing date 16.12.2013 Version number 3 Revision: 16.12.2013

Trade name: Osmo Maintenance Oil

(Contd. of page 6)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

64742-47-8 aliphatic hydrocarbons, C13-C18

LC50 / 96h 2.9 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

64742-48-9 aliphatic hydrocarbons, C10-C13

EC50 / 48h | > 1000 mg/l (daphnia) (OECD 202)

EC50/ 72h |> 1000 mg/l (algae) (OECD 201)

LC50 / 96h > 1000 mg/l (fish) (OECD 203)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential

64742-47-8 aliphatic hydrocarbons, C13-C18

log POW 7-8.7 (-)

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for

water

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.*vPvB*: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to reach

sewage system.

European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

15 01 10* packaging containing residues of or contaminated by dangerous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

(Contd. on page 8)



Printing date 16.12.2013 Version number 3 Revision: 16.12.2013

Trade name: Osmo Maintenance Oil

(Contd. of page 7)

SECTION 14: Transport information			
14.1 UN-Number			
ADR, ADN, IMDG, IATA	Void		
14.2 UN proper shipping name			
ADR, ADN, IMDG, IATA	Void		
14.3 Transport hazard class(es)			
ADR, ADN, IMDG, IATA			
Class	Void		
14.4 Packing group			
ADR, IMDG, IATA	Void		
14.5 Environmental hazards:			
Marine pollutant:	No		
14.6 Special precautions for user	Not applicable.		
14.7 Transport in bulk according to Anne	ex II of		
MARPOL73/78 and the IBC Code	Not applicable.		
UN "Model Regulation":	-		

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:

Not applicable. VOC(EC)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

H304 May be fatal if swallowed and enters airways. Relevant phrases

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

Department issuing MSDS: product safety department

Contact: Hr. Dr. Starp

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement Abbreviations and acronyms:

concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 9)



Printing date 16.12.2013 Version number 3 Revision: 16.12.2013

Trade name: Osmo Maintenance Oil

(Contd. of page 8)

 $\hbox{GHS: Globally Harmonized System of Classification and Labelling of Chemicals}$

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

* Data compared to the previous version altered.

GB